



- NOTES:
1. MATERIAL: C1008 BRIGHT BASIC WIRE.
  2. FINISH: (1) ZINC PLATING.  
(2) BLACK EPOXY POWDER COATING.
  3. (1) RINGS ARE  $\phi 2.7 \pm 0.1 \text{mm}$ .  
(2) RIBS ARE  $\phi 2.7 \pm 0.1 \text{mm}$ .
  4. WELD JOINTS TO WITHSTAND 88 LBS PULL FORCE.
  5.  $0.35 \pm 0.05$  DEPTH OF SERRATIONS ON WIRE.
  6. GENERAL TOLERANCE UNLESS NOTED:  $\pm 0.76 \text{mm}$ .
  7. ROHS COMPLIANT.
  8. UNIT: mm.

SPECIFICATION			
Motor	Speed (RPM)	Bearings	
Voltage (V)	Motor Protection	Weight (Kg)	
Frequency (Hz)	Insulation Class	Air Volume (M <sup>3</sup> /h)	
Power In/Out (W)	Protection Class	Noise Level (dBA)	
Current (A)	Temp. Range	Pressure (Pa)	

**POLE STAR**  
PRODUCTS LIMITED

POLE STAR PRODUCTS LIMITED	
Product Code	<b>WPG200</b>
Projection Angle	$\pm 3^\circ$
Sheet: 1 of	A4