



- NOTES:
1. MATERIAL: C1008 BRIGHT BASIC WIRE.
 2. FINISH: (1) ZINC PLATING.
(2) BLACK EPOXY POWDER COATING.
 3. (1) RINGS ARE $\phi 2.7 \pm 0.1 \text{mm}$.
(2) RIBS ARE $\phi 2.7 \pm 0.1 \text{mm}$.
 4. WELD JOINTS TO WITHSTAND 88 LBS PULL FORCE.
 5. 0.35 ± 0.05 DEPTH OF SERRATIONS ON WIRE.
 6. GENERAL TOLERANCE UNLESS NOTED: $\pm 0.76 \text{mm}$.
 7. ROHS COMPLIANT.
 8. UNIT: mm.

SPECIFICATION			
Motor	Speed (RPM)	Bearings	
Voltage (V)	Motor Protection	Weight (Kg)	
Frequency (Hz)	Insulation Class	Air Volume (M ³ /h)	
Power In/Out (W)	Protection Class	Noise Level (dBA)	
Current (A)	Temp. Range	Pressure (Pa)	

POLE STAR
PRODUCTS LIMITED

POLE STAR PRODUCTS LIMITED	
Product Code	WPG230
Projection Angle	$\pm 3^\circ$
	A4
	Scale:
	Sheet: 1 of