



	N	Abs. Pw	I	Lpa 3 m
	[RPM]	[kW]	[A]	[dB(A)]
(1)	1141	0,25	1,25	64.5
(2)	1134	0,30	1,51	60.5
(3)	1429	0,35	1,75	61.5

Air performance obtained in compliance with AMCA 210 and ISO 5801, Installation A category in VIP full nozzle and without guard grill.

Sound power levels and sound energy levels determined in accordance with ISO 3744. The uncertainty conforms to ISO 12001, accuracy grade 2.

Standard operating condition
 Continuous duty - S1
 International protection IP 55
 Voltage and frequency range in compliance with IEC 60034-1

ERP 2015
 $\eta_{A,Stat}$ 30,0 % Efficiency grade 29,8 %

Description	Part Number	□ L0	□ L1	ØD0	ØD1	H0	H1	H2	H3	Motor Frame	Kg
UH 035-36-4M-P-0X06Y-A	1400067	450	400	356	390	276	32	62	15	63 B14	5.5

Optimum energy Efficiency point

Input Power 0,248 Kw Pressure 88 Pa
 Air Flow 3025 m3/h RPM 1316 RPM

SPECIFICATION					
Motor	PSC	Speed (RPM)	1316	Bearings	Ball
Voltage (V)	230	Motor Protection	Th.Prot.	Weight (Kg)	5.5
Frequency (Hz)	50	Insulation Class	F	Noise dB(A)	61
Power In/Out (W)	248	Protection Class	IP55	Amb. Operation	-15 ~ +60
Current (A)	1.5	Capacitor (MF)	12	Max Op. Range	81

POLE STAR
 PRODUCTS LIMITED

POLE STAR PRODUCTS LIMITED

Product Code
PMAHD1-350S4-1

Projection Angle
 ± 3°



A4
 Scale:
 Sheet: 1 of