



Unit: axial fan motor	Customer: WFX055-NX
Insulation class: F	Operating type: S1
Permissible ambient temperature: -30~+60°C	Permissible temperature rise: <85K
Motor protection: thermocontact 155±5°C	Bearings: ball bearings
License: CE CCC RoHS	
High-voltage test according to EN 60335-1 1800V	
Electrical connection: lead wire 0.75mm².	
Direction of rotation : clockwise(sucking), counterclockwise (blowing), looking into fan guard.	
Material/Surface treatment : rotor with condensation drain holes varnished black, stator temperature protected	
Balance grade: G6.3. Fan balanced dynamically in two planes.	

SPECIFICATION					
Motor	3ph	Speed (RPM)	1350 min	Bearings	Ball
Voltage (V)	380	Motor Protection	Th. Prot	Weight (Kg)	9.2
Frequency (Hz)	50	Insulation Class	F	Air Volume (M³/h)	8500
Power In/Out (W)	750	Protection Class	IP54	Noise Level (dBA)	73
Current (A)	1.5	Temp. Range	-30 +60		

POLE STAR
PRODUCTS LIMITED

POLE STAR PRODUCTS LIMITED	
Product Code	
GMA3-500S-3	
Projection	A4
Angle	Scale:
± 3°	Sheet: 1 of